



Ideal transport aid for application in damp or harsh environments such as meat or fish processing plants, dairies, pharmaceutical and chemical industry.



GALVANIZED PALLET TRUCK

- All the exposed parts of the whole truck galvanized, including hydraulic pump, fork frame, handle and so on.
- Special application in cold and wet environments resists the effects of cold, condensation and washing.
- Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.
- With pressure relief valve and overload valve to prevent pump damages when loads exceed weight limits.
- The one-piece pump design simplifies repairs, assuring reliable service and long life.

| Galvanized pallet truck | | 1KG=2.2LB 1INCH=25.4MM | |
|---------------------------------|----|------------------------|----------|
| Item/Type | | ACZ20H | ACZ20L |
| Capacity Q | kg | 2000 | 2000 |
| Min. fork height h | mm | 85 | 75 |
| Max. fork height h ₁ | mm | 200 | 190 |
| Steering wheel | mm | φ 200x50 | φ 180x50 |
| Load roller Single | mm | φ 80x93 | φ 74x93 |
| Load roller Tandem | mm | φ 80x70 | φ 74x70 |
| Size of fork e*s | mm | 160x60 | |
| Width overall forks B | mm | 520/540/685 | |
| Fork length l | mm | 1100/1150/1220 | |

Conforms to EN 1757-2

STAINLESS PALLET TRUCK

| Stainless pallet truck | | 1KG=2.2LB 1INCH=25.4MM | |
|---------------------------------|----|------------------------|----------|
| Item/Type | | ACS20H | ACS20L |
| Capacity Q | kg | 2000 | 2000 |
| Min. fork height h | mm | 85 | 75 |
| Max. fork height h ₁ | mm | 200 | 190 |
| Steering wheel | mm | φ 200x50 | φ 180x50 |
| Load roller Single | mm | φ 80x93 | φ 74x93 |
| Load roller Tandem | mm | φ 80x70 | φ 74x70 |
| Size of fork e*s | mm | 160x60 | |
| Width overall forks B | mm | 520/540/685 | |
| Fork length l | mm | 1000/1100/1150/1220 | |

Conforms to EN 1757-2

- All metal parts made completely stainless steel, including hydraulic pump, fork frame, handle and so on.
- Ideal transport aid for application in damp or harsh environments such as meat or fish processing plants, dairies, pharmaceutical and chemical industry.
- With pressure relief valve and overload valve to prevent pump damages when loads exceeds weight limits.
- The enclosed fork tips (for Aisi316 stainless truck only) ensure there is no dead corner where corrosive spatters remains and damages the truck.
- Specially designed for applications where hygiene is of utmost importance.
- Nylon steering wheel and fork rollers as standard option for damp or harsh environments applications.



Hand Pallet Truck